

## CLADDING PANEL

A2, s1, d0 - Datum systems 3mm thk Solid Alum cassette cladding panel with Warrington fire certificate WF438098. Interpon D Fire PPC coated. See certificate RA19-0226

Panels secret fixed with 2No. Stainless Steel rivets or fixings in horizontal panel joint to each carrier rail into min 6.3mm Dia hole to allow for panel expansion. Also fixed point with 1No fixing at each carrier rail within horizontal panel joint.

## TYPICAL CAPPING

- 1 ) Sheathing board
- (2) Breather membrane
- (3) Additional Non flammable Insulation
- (4) Horizontal load spreader channel
- Helping hand brackets. Size determined by build up requirements
- (6) Helping hand T or L vertical mullion
- 7 Horizontal fire barriers with 25mm air gap
- (8) Capping flashing
- 9 Capping support flashing

75-80 North Netherton.	Datum Systems Limited  75-80 Northcott Road Wetherton, Dudley  A) Do not scale from this drawing.  B) All Dimensions shown on this drawing are in millimetres (mm)  C) Isolate all interfaces between aluminium and steel with barrier			Project: Datum Typical Details DTM 2	FOR INFORMATION		N	
Datum Systems Solutions made simple DY2 9PP	nds. (c) isolate all interfaces between aluminium and steel with partier tape			Drawing Title :	<u>Drawn</u> : MSD	<u>Date</u> : 15/05/25	Scale: N/A	Check: .
Tel: E-mail: sale	es@datumsystems.co.uk	A . MSC Rev. Date Inital	D Standard Issue	Typical Capping	<u>Drawing No.</u> : DTM1/2025 D05			Rev: A